





# Series Particulars

## SMD Aluminum Electrolytic Capacitor

Type	PIC	Series	Features	Standard	Low Impedance	Long Life	Load Life (Hours)	Operating Temperature Range (°C)	Rate Voltage Range (V.D.C.)	Capacitance Range (µF)
General Purpose		WXT	Standard 105°C 2000H	√			2000	-55~+105	4~100	0.1~2200
		WXS	Standard 85°C 2000H	√			2000	-40~+85	4~100	0.1~2200
Low Leakage Current		WSC	Low leakage current 105°C 2000H	√			2000	-40~+105	6.3~50	1~220
Bi-Polar		WCN	Bi-Polar 105°C 1000H	√			1000	-40~+105	6.3~50	1~100
		WVN	Bi-Polar 105°C 2000H	√			2000	-55~+105	6.3~50	1~100
Low Impedance		WRZ	Super Low ESR 105°C 2000H		√		2000	-55~+105	6.3~50	3.3~1500
		WRX	Super Low ESR 105°C 2000-5000H		√	√	2000~5000	-55~+105	6.3~50	10~2200
		WLZ	low impedance 105°C 2000H		√		2000	-55~+105	6.3~10 0	1~1500
		WFZ	low impedance 105°C 3000-5000H		√	√	3000~5000	-55~+105	6.3~10 0	4.7~1500



